



CS-Da Capo
Item #: 11602



Features


- The classical stereo styling design combines functionality and elegance
- High Quality Aluminium front panel (with black acrylic), also Aluminium top cover and side doors!
- Perfectly secured against thieves: Front door can be secured with lock, also including chassis intrusion detector
- Good EMI shielding for CE-compliant systems
- Removable installation cage for the open 3½" drives
- Transversal HDD cooling with 80 mm fan (optional with fan)
- Up to 5 fans (2× 80 mm + 3× 90 mm) can be installed

Technical Data:

- | | | | |
|--------------------------|--|---------------------------|--|
| • Quantity of 5¼"-bays: | 5 | • Powersupply (optional): | PS/2 |
| • Quantity of 3½"-bays: | 5 (2 x open + 3 x hidden) | • Accessories: | Various screw sets, standing feet, drive guide rails for screw less installation, PCI-card quick-release, washable fan dust filter |
| • Fans: | 2×80mm fans (1× in front, 1× on top), 3×90mm fans (2× sideways, 1× in rear) | | |
| • Expansion slots: | 7 | | |
| • Additional connectors: | 2× USB, 2× audio and 1x IEEE 1394 Firewire on Top | | |
| • Supported main boards: | Standard ATX, Extended ATX | | |

Logistic Data

- | | | | |
|----------------------------------|--------------------|--|--|
| • Quantity per 40' HC container: | 685 | | |
| • Quantity per 20' container: | 283 | | |
| • Quantity per palette: | 14 | | |
| • Net weight: | 10.10 kg | | |
| • Gross weight: | 12.10 kg | | |
| • Net dimensions (W × H × D): | 215 × 490 × 600 mm | | |
| • Gross dimensions (W × H × D): | 262 × 545 × 666 mm | | |
| • Custom tariff number: | 84733090 | | |
| • Country of origin: | PR China | | |
| • Case chassis material: | 1.0 SECC | | |
| • Case panel material: | Aluminium/Acrylic | | |
| • Case chassis colour: | Silver | | |
| • Case panel colour: | Silver/Black | | |
| • EAN barcode: | 4250078101659 | | |



Easy installation
Cages for 5.25"/3.5"
sliding guide rail



Security
Internal key lock for
side panel to secure
from intrusion



Roof console
With connectors for USB,
IEEE 1394, microphone,
and headphones

Errors and technical modifications excepted — As of 09/2005